

1	2	3	4	5	6	7	8	9	10	11																																																														
符合"DLK环境管理物质技术标准"							工程变更通知单 ECN(DCN) NO.		版本 REV		日期 DATE		说明 DESCRIPTION		改变 CHANGE		承认 APPRO.																																																							
符合"IEC协会标准"							KSECN13067		A		20131227		NEW RELEASE		—		—																																																							
#4-40 THREAD MAX TORQUE RECOMMENDED PCB LAYOUT TOLERANCE: ±0.05mm 10.5H DLK 0.60 1.98 1.98 3.78 8.49 NOTE: 1. MATERIAL: 1.1 Housing/Cover: PBT UL94v-0, color: Blue 1.2 Contact: Copper alloy 1.3 Shell: Ferro alloy 1.4 Rivet Insert:Ferro alloy 1.5 Rivet: Copper alloy 2. PLATING: 2.1 Contact: 1u"Au plated on contact Area, 100u" Min. Tin plated on solder tail, 50u" Min.Nickel underplated 2.2 Shell: Nickel plated overall 3. MECHANICAL: 3.1 Insertion force:2.0~5.0kgf. 3.2 Withdrawal force:1.0Kgf Min. 3.3 Durability:500 cycles Min. 4 ELECTRICAL: 4.1 Current Rating:1.0A 4.2 Voltage Rating:36V 4.3 Dielectric strength:500V AC FOR 1 minute 4.4 Insulation Resistance:1000MΩ Min. 4.5 Contact Resistance:30mΩ Max 5. Operating Temperature:-55°c to +105°c 6. PACKING: Tray																																																																								
							<table><tr><td colspan="2">GENERAL TOLERANCE UNLESS OTHERWISE NOTED</td><td colspan="2"></td><td colspan="2">德力康电子科技有限公司</td></tr><tr><td colspan="2">Angle ±5°</td><td colspan="2">DLK</td><td colspan="2">DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD</td></tr><tr><td colspan="2">X. ±0.35</td><td colspan="2">C 名称 TITLE:</td><td colspan="2">D-SUB V/T 10. 5H CONN.</td></tr><tr><td colspan="2">.X ±0.25</td><td colspan="2">档案名称 FILE NAME.</td><td colspan="2">C-DSB46-00-07</td></tr><tr><td colspan="2">.XX ±0.15</td><td colspan="2">料号 PART NO:</td><td colspan="2">84615L21370</td></tr><tr><td colspan="2">.XXX ±0.10</td><td colspan="2">DRAWING</td><td colspan="2">王永辉</td></tr><tr><td colspan="2">A4</td><td colspan="2">UNIT:</td><td colspan="2">mm</td></tr><tr><td colspan="2"></td><td colspan="2">SCALE</td><td colspan="2">1:1</td></tr><tr><td colspan="2"></td><td colspan="2">SHEET:</td><td colspan="2">1 of 1</td></tr></table>												GENERAL TOLERANCE UNLESS OTHERWISE NOTED				德力康电子科技有限公司		Angle ±5°		DLK		DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD		X. ±0.35		C 名称 TITLE:		D-SUB V/T 10. 5H CONN.		.X ±0.25		档案名称 FILE NAME.		C-DSB46-00-07		.XX ±0.15		料号 PART NO:		84615L21370		.XXX ±0.10		DRAWING		王永辉		A4		UNIT:		mm				SCALE		1:1				SHEET:		1 of 1	
GENERAL TOLERANCE UNLESS OTHERWISE NOTED				德力康电子科技有限公司																																																																				
Angle ±5°		DLK		DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD																																																																				
X. ±0.35		C 名称 TITLE:		D-SUB V/T 10. 5H CONN.																																																																				
.X ±0.25		档案名称 FILE NAME.		C-DSB46-00-07																																																																				
.XX ±0.15		料号 PART NO:		84615L21370																																																																				
.XXX ±0.10		DRAWING		王永辉																																																																				
A4		UNIT:		mm																																																																				
		SCALE		1:1																																																																				
		SHEET:		1 of 1																																																																				
							<table><tr><td>6</td><td>RIVET</td><td>2</td><td>COPPER ALLOY</td><td>Ni PLATED</td></tr><tr><td>5</td><td>RIVET INSERT</td><td>2</td><td>FERROALLOY</td><td>Tin PLATED</td></tr><tr><td>4</td><td>CONTACT</td><td>15</td><td>COPPER ALLOY</td><td>Au AND Tin PLATED</td></tr><tr><td>3</td><td>SHELL</td><td>1</td><td>FERROALLOY</td><td>Ni PLATED</td></tr><tr><td>2</td><td>COVER</td><td>1</td><td>PBT</td><td>UL94V-0</td></tr><tr><td>1</td><td>HOUSING</td><td>1</td><td>PBT</td><td>UL94V-0</td></tr><tr><td>NO.</td><td>ITEM</td><td>Q'TY</td><td>DESCRIPTION</td><td>FINISH</td></tr></table>												6	RIVET	2	COPPER ALLOY	Ni PLATED	5	RIVET INSERT	2	FERROALLOY	Tin PLATED	4	CONTACT	15	COPPER ALLOY	Au AND Tin PLATED	3	SHELL	1	FERROALLOY	Ni PLATED	2	COVER	1	PBT	UL94V-0	1	HOUSING	1	PBT	UL94V-0	NO.	ITEM	Q'TY	DESCRIPTION	FINISH																			
6	RIVET	2	COPPER ALLOY	Ni PLATED																																																																				
5	RIVET INSERT	2	FERROALLOY	Tin PLATED																																																																				
4	CONTACT	15	COPPER ALLOY	Au AND Tin PLATED																																																																				
3	SHELL	1	FERROALLOY	Ni PLATED																																																																				
2	COVER	1	PBT	UL94V-0																																																																				
1	HOUSING	1	PBT	UL94V-0																																																																				
NO.	ITEM	Q'TY	DESCRIPTION	FINISH																																																																				
1	2	3	4	5	6	7	8	9	10	11																																																														