







符合"DLK环境管理物质技术标准"

符合VESA协会规范标准"



RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05mm



工程变更通知单 ECN(DCN) NO.	版本 REV	日期 DATE	说明 DESCRIPTION	变更 CHANGE	核准 APPRO.
KSECN19032	A	20190701	NEW RELEASE	—	—
KSECN21056	B	20211110	配合自动机外护套增加倒角 Δ *1	蒋召	吴豪

NOTE:

1. MATERIAL.

1.1 Housing: LCP UL94v-0, color: Black

1.2 Contact: Copper alloy

1.3 Shell: Stainless steel

2. PLATING:

2.1 Contact: 1u"Au plated on contact Area,
50u" Min. Matte Tin plated on solder tail,
50u" Min. Nickel underplated

2.2 Shell: Nickel plated overall

3. MECHANICAL:

3.1 Mating force: 4.5kgf Max.

3.2 Unmating force: 1.0~4.0kgf.

3.3 Durability: 10000 cycles Min.

4 ELECTRICAL:

4.1 Current Rating: 0.5A

4.2 Voltage Rating: 40V

4.3 Dielectric strength: 500V AC FOR 1 minute

4.4 Insulation Resistance: 100MΩ Min.

4.5 Contact Resistance: 30mΩ Max

5. Operating Temperature: -55°C to +85°C

6. PACKING: Tray

4	JACKET	1	LCP	UL94V-0,Black
3	CONTACT	20	COPPER ALLOY	PLATED Au
2	SHELL	1	STAINLESS STEEL	PLATED NI
1	HOUSING	1	LCP	UL94V-0,Black
NO.	ITEM	Q'TY	DESCRIPTION	FINISH

GENERAL TOLERANCE UNLESS OTHERWISE NOTED	
Angle	±5°
X.	±0.35
.X	±0.25
.XX	±0.15
.XXX	±0.10
A4	

德力康电子科技有限公司
DLK DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD

C	名称 TITLE:	DisplayPort DIP Type 14H (无后塞)			
	档案名称 FILE NAME:	C-DPT21-00-02	料号 PART NO:	62120B01121	
DRAWING	覃智森	CHECKED	王永辉	APPROVED	严成旺
UNIT:	mm	SCALE	1:1	SHEET: 1 of 1	