

符合"DLK环境管理物质技术标准"

符合VESA协会规范标准"

工程变更通知单 ECN(DCN) NO.	版本 REV	日期 DATE	说明 DESCRIPTION	改变 CHANGE	承认 APPRO.
KSECN22039	A	20220919	NEW RELEASE	——	——
KSECN23020	B	20230703	依客户要求将凸台加胶与塑胶齐平	邱 宇	吴 豪

NOTE:

1. MATERIAL.

1.1 Housing: LCP UL94v-0, color: Black

1.2 Contact: Copper alloy

1.3 Shell: Stainless steel

2. PLATING:

2.1 Contact: 1u"Au plated on contact Area,
50u" Min. Matte Tin plated on solder tail,
50u" Min. Nickel underplated

2.2 Shell: Nickel plated overall

3. MECHANICAL:

3.1 Mating force:4.5kgf Max.

3.2 Unmating force:1.0~4.0kgf.

3.3 Durability:10000 cycles Min.

4 ELECTRICAL:

4.1 Current Rating:0.5A

4.2 Voltage Rating:40V

4.3 Dielectric strength:500V AC FOR 1 minute

4.4 Insulation Resistance:100MΩ Min.

4.5 Contact Resistance:30mΩ Max

5. Operating Temperature:-55°c to +85°c

6. PACKING: Tape & Reel

 德力康电子科技有限公司
DLK DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD

GENERAL TOLERANCE UNLESS OTHERWISE NOTED		C 名称 TITLE:	DisplayPort SMT Type 180D 15H DIP脚长1.9			
Angle	±5°	档案名称 FILE NAME.	C-DPT2A-00-13	料号 PART NO:	62A20B01131	
X.	±0.35	DRAWING	覃智森	CHECKED	——	APPROVED 吴 豪
.X	±0.25	UNIT:	mm	SCALE	1:1	SHEET: 1 of 1
.XX	±0.15					
.XXX	±0.10					
A4						