



* Images may differ from the real thing.

SFTL-6P-24V-4A2B

Number of poles: 6

Applicable Relay : SFS4-DC24V: 4A2B, SFS5-DC24V: 5A1B, SFS6-DC24V: 3A3B

Terminal Type : Screwless

Stripping length : 8 ~ 10 mm

Material: CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL

Add products of interest

- [Find a Distributor](#)
- [Compare](#)
- [View model specs](#)

Data Sheet

Pole water	6
Relay	SFS4-DC24V: 4A2B, SFS5-DC24V: 5A1B, SFS6-DC24V: 3A3B
Rated voltage	24VDC±10% $\overline{\text{---}}$
Rated Load Voltage	250 VAC~ 50/60 Hz, 30 VDC $\overline{\text{---}}$
Continuous Currents	6A
Light	Action Indicator: Green
Terminal Type	Screwless
Stripping length of wire stripping	8 ~ 10 mm

Insulation Resistance	≥ 1,000 MΩ (500VDC megger)---
Withstand Voltage_Between Coil to Contact	4,000 VAC~ 50/60 Hz for 1 minute
Withstand voltage_between two pole contacts	2,500 VAC~ 50/60 Hz for 1 minute
Withstand voltage_to-copper contact	2,500 VAC~ 50/60 Hz for 1 minute
Vibration resistant	10 ~ 55 Hz Double Amplitude 0.75 mm X, Y, Z direction 2 hours each
Shock	300 m/s ² (≈ 30 G) X, Y, Z 3 times each
Ambient temperature	-25 ~ 70 °C, when preserved: -30 ~ 80 °C (no freezing or condensation)
Ambient humidity	25 ~ 85 % RH, when preserved: 25 ~ 85 % RH (no freezing or condensation)
Protective Structure	IP20 (IEC compliant)
material	CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL
Body weight (packaging)	≈ 51.2 g (≈ 99.2 g)

3D Viewer

* Click the CAD button below the product image at the top of the page to check out the 3D Viewer.

Flyer

Promotional materials can be downloaded without logging in.



catalog

Catalogs 2023-...



Brochure

Safety range

View in original I...

View in original I...

download

Snippets

download

Snippets



1



Technical Resources

More

whole 7

manual 2

CAD 2

certificate 3

software 0

Detailed model-specific 3D drawings can be viewed and downloaded on the model page below.

manual >
Instruction manual

View in ori...

PDF

SFT Series

manual >
Product Manuals

View in ori...

PDF

SFT Series



1

