**Date:** 04.09.2024

Title: Datasheet and Design Guide Update / Clarification

**Product Identification: STC31-C** 

**Information Letter Number: 243601** 

## **Change Description:**

There are no changes to the actual product. These updates include minor formatting and misspelling corrections, added details for handling specific responses, and important clarifications on measurement modes

## Datasheet:

| Date          | Version | Pages / Sec-<br>tions | Changes  |
|---------------|---------|-----------------------|--|
| Sept.<br>2024 | 3.2     | all                   | Minor corrections of spelling and format   |
|               |         | 3.2                   | Added additional information for handing NACK response to CRC byte   |
|               |         | 3.3.7                 | Added clarification: The resulting correction is only valid for the active measurement mode, binary gas and range. |

Design Guide:

| Date           | Version | Section | Changes   |
|----------------|---------|---------|---|
|                | 1.2     | 4.1     | Notice: The resulting correction is only valid for the active measurement mode, binary gas and range.   |
| September 2024 |         | 6.2.2   | Notice added: Oxygen sensitivity of the low-cross-<br>sensitivity measurement mode is much lower than for<br>the low-noise mode. However, it does<br>not correct within specifications and needs to be<br>validated for the specific application. |

Estimated Implementation Date: Immediately, new documents are available