

MATERIALS & SPECIFICATIONS

INSULATOR:
LIQUID CRYSTAL POLYMER (LCP) PER ASTM
D5138

ORGANIZER BLOCK:
LIQUID CRYSTAL POLYMER (LCP) PER ASTM
D5138

CONTACT:
COPPER ALLOY PER MIL-DTL-83513, GOLD
PLATED PER ASTM B488, (HARD GOLD)
TYPE II CODE C, CLASS 1.27

TERMINATION:
SOLDER COATED WITH SN63A PER J-STD-
006 OR AMS-P-81728




CURRENT CAPACITY:
3 AMP MAX PER MIL-DTL-83513

CONTACT RESISTANCE:
26 MILLIOHMS (85 mV) MAX @ 2.5 AMPS
PER MIL-DTL-83513



PERFORMANCE:
PRODUCT FAMILY TESTED TO AND PASSED
THE PERFORMANCE SPECIFICATIONS OF
TABLE VII OF MIL-DTL-83513



ACTUAL SIZE



PART NO.	REV	ECO	DATE	APP
A22060-001	C	100726	07-17-14	TLM



NOTE:

TAIL DIMENSIONS APPLY
AT PLANE A

DIMENSIONS IN [] ARE IN
MILLIMETERS UNLESS
OTHERWISE NOTED AND ARE
FOR REFERENCE ONLY

MCS STW	THIRD ANGLE DRAWING		WE DRAW NO CONTINGENT, AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OWNER/CONNECTION CORP. THIS DOCUMENT MAY NOT BE IN WHOLE OR IN PART, BE DUPLICATED, REPRODUCED FOR ANY PURPOSE, WITHOUT IN WRITING PERMISSION FROM OWNER/CONNECTION CORP.	
	TOLERANCES		TITLE:	
	UNLESS OTHERWISE NOTED			
	DIMENSIONAL TOLERANCES		DFTM. NDP	
	2 PL DEC : 01		DATE 02-09-10	
	3 PL DEC : .005		DATE	
	4 PL DEC : .0005		CHKD.	
	ANGLES : 1°		DATE	
			APPD.	