








THIS IS A RoHS
COMPLIANT
COMPONENT/
PRODUCT.



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 100 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 1000 MEGOHMS MIN. @ 500 VDC.
5. DIELECTRIC STRENGTH : 750 VAC 60Hz, 1MIN.

MECHANICAL:

1. HOUSING MATERIAL : PC UL94V-0.
2. INSERT MATERIAL : PBT+30% GF. UL94V-0.
3. PCB MATERIAL : FR-4 THICKNESS 1.6 mm.
4. CONTACT MATERIAL : PHOSPHOR BRONZE STAMP PIN t=0.35 mm
5. IDC CONTACT MATERIAL : PHOSPHOR BRONZE t=0.50 mm WITH NICKEL PLATING
6. WIRE : #24~26 AWG

ENVIRONMENTAL:

1. STORAGE : -40°C TO +85°C.
2. OPERATION : 0°C TO 70°C.

MARK	ECN-NO.	NEW DESIGE	HENRY	121014'
		REVISION RECORD	DRAWN	DATE
		UNLESS OTHERWISE SPECIFIED TOLERANCE	SCALE	CHECKED
		Dimension Range Tolerance	1/1	
		X.X ±0.20	UNIT	mm
		X.XX ±0.15		APPROVED
		X.XXX ±0.10	SIZE	A3
Material/Plated/Notes		ANGLE	±5°	
SEE NOTE		NAME		
		Cat.5e SIDE ENTRY KEYSTONE JACK		
Tooling No.		PART NO.	326I-0008-05	REV.
		DOC. NO.		1

Design drawing