

Style
M12 Socket, shielded
5 pin
A-coding

Ratings
Voltage: 60 V
Current: 4 A

Operating Temperature Range
-40~105°C


Materials
① Insulator: Polyamide 66 (PA66), UL94 HB, black
② Pin: Phosphor copper, gold flashing
③ M12 Shell: Brass, nickel plated
④ O-ring: Nitrile rubber, black & green
⑤ Epoxy: Epoxy resin

Electrical Requirements
Insulation resistance: 100 MΩ @ 500 Vdc
Contact resistance: 10 mΩ or less


Mechanical Requirements
Life cycle: 500 mating cycles minimum

Environmental Requirements
Salt spray test: 35 °C, relative humidity 90-95%, 5% NaCl mist for 48 hrs. Wash parts after test. Maintain mechanical requirements and a contact resistance of less than 10 mΩ.
Waterproof: IP67




Assembly info
Wire gauge: 22 AWG max




Front View
Not to Scale





SECTION A-A



Panel cut-out
Not to Scale



Revision:	Date:	Description:	Prepared:	Notes:	<div>TENSILITY</div> <div>tel 1.541.323.3228 800 877.670.7118</div> <div>fax 1.541.323.4202 web tensility.com</div>			
A	04/05/2024	Initial release	Verified:	RoHS compliant				
			Dimensions are in millimeters. Tolerances: X: ± 0.3 mm X.X: ± 0.1 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent				
				Description: Connector, 5 pin M12 A-code socket, 12xL21.8mm, gold plated, flange mount, solder cup, IP67, shielded	Size:	Part number:		
					A	55-00233		
					Scale: 2:1			Sheet 1 of 1