

**IEC Mineral Insulated Thermocouple Type K
Stainless Steel 1.5 x 500mm Threaded Pot
100mm PFA Twin Twisted Bare Tails**

XE-3313-001



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockists of Thermocouple Cables. The Company has been trading since 1971 and is ISO 9001 accredited.

Specifications

General Description	Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC, 7/0.2mm.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	1.5mm
Probe Length	500mm
Sheath Material	K - Stainless steel 310
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC
Core / Strands	7/0.2mm
Termination Type	Bare tails
Max. Temperature	K +1100°C
Min. Temperature	K -40°C
Standards Met	In accordance with IEC 584

Ordering Information

Thermocouple Type	Colour Code	Size	Order Number
K	IEC	1.5mm x 500mm	XE-3313-001