



159 Ort Lane
Merlin, OR, US 97532
Phone: + 1 541 471 6256
Fax: + 1 541 471 6251
www.linstechnologies.com

October 4, 2013

To: All customers using the TXE-315-KH2, TXE-418-KH2 or TXE-433-KH2

Re: Product Change Notice

Dear customer,

Linux Technologies is announcing the End of Life for the TXE-***-KH2 product line and the introduction of the TXE-***-KH3 product line.

The end of life is a result of the discontinuance of critical components from Holtek®. The KH3 product line incorporates the Linux DS Series Encoder/Decoder IC, providing backwards compatibility for the majority of KH2 applications.

We are committed to working closely with our customers during the transition to address any questions or concerns.

Wireless made simple®

Product Change Notice for TXE-315-KH2, TXE-418-KH2 or TXE-433-KH2

PCN #: LPCN-131004-1

Publish Date: October 4, 2013

Type of Change

End of life notice for the KH2 product line and introduction of the KH3 product line.

Products Affected

TXE-315-KH2

TXE-418-KH2

TXE-433-KH2

Description of Change

The HT640 Encoder used in the previous version of the KH2 product line has gone end-of-life by the manufacturer (Holtek)[®]. The KH2 product line has been redesigned to incorporate the Linx DS series encoder, and is being introduced as the KH3 product line. The design change provides for backwards compatibility with existing fielded devices using the Holtek[®] dip switch addressing scheme.

The new generation of product offers additional functionality and optional configuration pins, resulting in a new naming convention for the product line. The KH3 product will fit in the PCB footprint for those customers who have followed Linx recommended layout guidelines for the KH2 product – the additional pins would be unused and non-connected.

Reason for Change

Component end-of-life.

Effect of Change

Form: 3 additional pins added to support address interpretation

Fit: No change to overall module size

Function: No support for tri-state addressing

Quality: No change

Anticipated First Ship Date

Samples available December 2013

Qualification Data

Qualification plan specifics are not for general release. Please contact Linx directly for additional information or assistance.

Last Time Buy Date

No formal last time buy date is established.

Specification Comparison

ELECTRICAL SPECIFICATIONS		TXE-***-KH3			TXE-***-KH2			Units	Notes
POWER SUPPLY		Min.	Typical	Max.	Min.	Typical	Max.		
Operating Voltage	V_{CC}	2.7		5.2	2.7		5.2	VDC	-
Supply Current	I_{CC}		1.5			1.5		mA	1,2,3,5
Power-Down Current	I_{PDN}		1.0			1.0		μ A	5
TRANSMITTER SECTION									
Transmit Frequency	F_C								
TXE-315-KH3/2			315			315		MHz	-
TXE-418-KH3/2			418			418		MHz	-
TXE-433-KH3/2			433.92			433.92		MHz	-
Center Frequency Accuracy	-	-75	-	+75	-75	-	+75	kHz	2, 5
Output Power	P_O	-4	-1	+4	-4	+2	+4	dBm	2,3,4
Harmonic Emissions	P_H								
TXE-315-KH3/2				-36			-36	dBc	2
TXE-418-KH3/2				-36			-36	dBc	2
TXE-433-KH3/2				-36			-36	dBc	2
ANTENNA PORT									
RF Output Impedance	R_{OUT}		50			50		Ω	4
ENCODER									
Data Length	-								
Holtek® Protocol			26 bits 3x			26 bits 3x			
DS Serial Protocol						-		-	
Average Duty Cycle	-	-	50%	-	-	50%	-	-	4
Encoder Oscillator	F_{ENC}	-	N/A	-	-	70	-	kHz	
Data Input									
Logic Low	V_{IL}	0	-	$0.2 \times V_{CC}$	0	-	$0.2 \times V_{CC}$	VDC	4
Logic High	V_{IH}	$V_{CC} \times 0.8$	-	V_{CC}	$V_{CC} \times 0.8$	-	V_{CC}	VDC	4
Input Sink Current	-	-	0.0001	0.005	0.6	1.0	1.2	mA	4
ENVIRONMENTAL									
Operating Temperature Range	-	-30	-	+70	-30	-	+70	°C	-

Notes:

1. Current draw with 50% mark / space ratio.
2. Into a 50 ohm load.
3. With 430 ohm resistor on LADJ.
4. Characterized, but not tested.
5. At 25°C, with 3V supply.

Footprint Comparison




Figure 1a: TXE-***-KH3 Footprint




Figure 1b: TXE-***-KH2 Footprint