VE-300 & VE-5003

Readability **0.001 g / 0.001 g**





- · High contrast LCD screen.
- Robust ABS housing.
- · Leveling feet.
- · Multiple weighing units.

















- Internal rechargeable battery.
 - · Large stainless steel pan.
 - RS 232 interface.
 - · 3 Door anti-static draft shield

▶ Standard Functions

- · Weighing.
- · Parts counting.
- · Percentage weighing.

Overall Dimensions

Power Supply

Net Weight Warranty · Accumulation.

► Accesories Included

· RS-232 cable.

· Calibration weight.

280 x 190 x 265 mm / 11" x 7.5" x 10.4"

CA 110/240V, 50/60 Hz and rechargeable battery.

4.2 Kg / 9.5 lbs.

1 year.

TECHNICAL DATA		
Model	VE-300	VE-5003
Capacity	300 g	400 g
Readability	0.001 g	0.001 g
Repeatability	±0.001 g	±0.001 g
Linearity	±0.002 g	±0.002 g
Weighing Units	g, ct, oz, ozt, dwt, t, N, GN, T/A/R	
Calibration	External.	
Pan Size	Ø80mm / 3.1"	
Stabilization Time	≤ 2 seconds	
Interface	RS-232.	
Display	LCD, digit height 19mm / 0.7"	
Housing	ABS plastic.	
Operating Environment	10° to 30°C / 50° to 85°F / Humidity 20% - 80%	