

Shield connection clamp - SK 20-D - 3026887

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Shield connection clamp, for direct shield on conductive mounting plates, metal thickness 1 ... 2 mm

Your advantages

- ✓ Easy handling
- ✓ Spring-loaded, large-surface pressure plate
- ✓ Suitable for direct and busbar mounting
- ✓ Knurled screw
- ✓ Knurled screw
- ✓ Spring-loaded, large-surface pressure plate

RoHS

Key Commercial Data

Packing unit	10 pc
GTIN	 4 017918 820275
GTIN	4017918820275

Technical data

General

Number of levels	1
Number of connections	1
Cable diameter	5 mm ... 20 mm
Color	silver
Open side panel	No

Dimensions

Length	19.5 mm
Width	24 mm
Height	73.5 mm

Connection data

Shield connection clamp - SK 20-D - 3026887

Technical data

Connection data

Connection method	Screw connection
Screw thread	M4
Tightening torque max	0.8 Nm

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		7500651.22.01.00246
-----	---	---------------------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>