

Dual N-Channel 30-V (D-S) MOSFET

PRODUCT SUMMARY				
	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A) ^a	Q _g (Typ.)
Channel 1	30	0.0145 at V _{GS} = 10 V	10.8	8.3
		0.0195 at V _{GS} = 4.5 V	9.3	
Channel 2	30	0.0265 at V _{GS} = 10 V	7.2	4
		0.036 at V _{GS} = 4.5 V	6.2	

FEATURES


- Halogen-free According to IEC 61249-2-21 Available
- TrenchFET[®] Power MOSFET
- 100 % R_g Tested





RoHS
COMPLIANT
HALOGEN
FREE
Available

APPLICATIONS

- Logic DC/DC for Notebook PC



Ordering Information: Si4972DY-T1-E3 (Lead (Pb)-free)
Si4972DY-T1-GE3 (Lead (Pb)-free and Halogen-free)



ABSOLUTE MAXIMUM RATINGS $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted					
Parameter		Symbol	Channel 1	Channel 2	Unit
Drain-Source Voltage		V_{DS}	30		V
Gate-Source Voltage		V_{GS}	± 20		
Continuous Drain Current ($T_J = 150\text{ }^{\circ}\text{C}$)	$T_C = 25\text{ }^{\circ}\text{C}$	I_D	10.8	7.2	A
	$T_C = 70\text{ }^{\circ}\text{C}$		8.7	5.7	
	$T_A = 25\text{ }^{\circ}\text{C}$		8.7 ^{b,c}	6.4 ^{b,c}	
	$T_A = 70\text{ }^{\circ}\text{C}$		6.9 ^{b,c}	5.1 ^{b,c}	
Pulsed Drain Current (10 μ s Pulse Width)		I_{DM}	20	20	
Source-Drain Current Diode Current	$T_C = 25\text{ }^{\circ}\text{C}$	I_S	2.5	2.1	
	$T_A = 25\text{ }^{\circ}\text{C}$		1.6 ^{b,c}	1.6 ^{b,c}	
Pulsed Source-Drain Current		I_{SM}	20	20	
Single Pulse Avalanche Current	$L = 0.1\text{ mH}$	I_{AS}	15	6	mJ
Avalanche Energy		E_{AS}	11	1.8	
Maximum Power Dissipation	$T_C = 25\text{ }^{\circ}\text{C}$	P_D	3.1	2.5	W
	$T_C = 70\text{ }^{\circ}\text{C}$		2.1	1.6	
	$T_A = 25\text{ }^{\circ}\text{C}$		2.0 ^{b,c}	2.0 ^{b,c}	
	$T_A = 70\text{ }^{\circ}\text{C}$		1.25 ^{b,c}	1.25 ^{b,c}	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	- 55 to 150		$^{\circ}\text{C}$

THERMAL RESISTANCE RATINGS

Parameter		Symbol	Channel 1		Channel 2		Unit
			Typical	Maximum	Typical	Maximum	
Maximum Junction-to-Ambient ^{b, d}	t ≤ 10 s	R _{thJA}	52	62.5	55	62.5	°C/W
Maximum Junction-to-Foot (Drain)	Steady	R _{thJF}	32	40	40	50	

Notes:

- Based on T_C = 25 °C.
- Surface mounted on 1" x 1" FR4 board.
- t = 10 s.
- Maximum under steady state conditions is 110 °C/W (Ch 1) and 120 °C/W (Ch 2).

SPECIFICATIONS $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions	Min.	Typ. ^a	Max.	Unit	
Static							
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$	Ch 1	30		V	
		$V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$	Ch 2	30			
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = 250\text{ }\mu\text{A}$	Ch 1		35	mV/ $^{\circ}\text{C}$	
		$I_D = 250\text{ }\mu\text{A}$	Ch 2		35		
$V_{GS(th)}$ Temperature Coefficient	$\Delta V_{GS(th)}/T_J$	$I_D = 250\text{ }\mu\text{A}$	Ch 1		- 6.5		
		$I_D = 250\text{ }\mu\text{A}$	Ch 2		- 6.5		
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	Ch 1	1.5	3.0	V	
		$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	Ch 2	1.5	3.0		
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$	Ch 1 Ch 2		100 100	nA	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}$	Ch 1		1	μA	
		$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}$	Ch 2		1		
		$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}, T_J = 55\text{ }^{\circ}\text{C}$	Ch 1		10		
		$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}, T_J = 55\text{ }^{\circ}\text{C}$	Ch 2		10		
On-State Drain Current ^b	$I_{D(on)}$	$V_{DS} = 5\text{ V}, V_{GS} = 10\text{ V}$	Ch 1	10		A	
		$V_{DS} = 5\text{ V}, V_{GS} = 10\text{ V}$	Ch 2	10			
Drain-Source On-State Resistance ^b	$R_{DS(on)}$	$V_{GS} = 10\text{ V}, I_D = 6\text{ A}$	Ch 1		0.012	Ω	
		$V_{GS} = 10\text{ V}, I_D = 4.5\text{ A}$	Ch 2		0.022		
		$V_{GS} = 4.5\text{ V}, I_D = 5.6\text{ A}$	Ch 1		0.016		
		$V_{GS} = 4.5\text{ V}, I_D = 4\text{ A}$	Ch 2		0.030		
Forward Transconductance ^b	g_{fs}	$V_{DS} = 15\text{ V}, I_D = 6\text{ A}$	Ch 1		27	S	
		$V_{DS} = 15\text{ V}, I_D = 4.5\text{ A}$	Ch 2		20		
Dynamic ^a							
Input Capacitance	C_{iss}	Channel 1 $V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$ Channel 2 $V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$	Ch 1 Ch 2		1080 515	pF	
Output Capacitance	C_{oss}		Ch 1 Ch 2		170 91		
Reverse Transfer Capacitance	C_{rss}		Ch 1 Ch 2		72 38		
Total Gate Charge	Q_g	$V_{DS} = 15\text{ V}, V_{GS} = 10\text{ V}, I_D = 5\text{ A}$	Ch 1 Ch 2		18.5 9.6	nC	
		$V_{DS} = 15\text{ V}, V_{GS} = 10\text{ V}, I_D = 5\text{ A}$			28 15		
		Channel 1 $V_{DS} = 15\text{ V}, V_{GS} = 4.5\text{ V}, I_D = 5\text{ A}$	Ch 1 Ch 2		8.3 4		13 6
Gate-Source Charge	Q_{gs}	Channel 2 $V_{DS} = 15\text{ V}, V_{GS} = 4.5\text{ V}, I_D = 5\text{ A}$	Ch 1 Ch 2		3.9 1.9		
Gate-Drain Charge	Q_{gd}		Ch 1 Ch 2		2.7 1.3		
Gate Resistance	R_g		$f = 1\text{ MHz}$	Ch 1 Ch 2			2.5 2.9









SPECIFICATIONS T _J = 25 °C, unless otherwise noted							
Parameter	Symbol	Test Conditions		Min.	Typ. ^a	Max.	Unit
Dynamic ^a							
Turn-On Delay Time	t _{d(on)}	Channel 1 V _{DD} = 15 V, R _L = 3 Ω I _D ≅ 5 A, V _{GEN} = 10 V, R _g = 1 Ω	Ch 1		12	18	ns
			Ch 2		10	15	
Rise Time	t _r		Ch 1		55	83	
			Ch 2		60	90	
Turn-Off DelayTime	t _{d(off)}	Channel 2 V _{DD} = 15 V, R _L = 3 Ω I _D ≅ 5 A, V _{GEN} = 10 V, R _g = 1 Ω	Ch 1		30	45	
			Ch 2		22	33	
Fall Time	t _f		Ch 1		7	11	
			Ch 2		6	9	
Turn-On Delay Time	t _{d(on)}	Channel 1 V _{DD} = 15 V, R _L = 3 Ω I _D ≅ 5 A, V _{GEN} = 4.5 V, R _g = 1 Ω	Ch 1		120	180	
			Ch 2		108	162	
Rise Time	t _r		Ch 1		150	225	
			Ch 2		130	195	
Turn-Off Delay Time	t _{d(off)}	Channel 2 V _{DD} = 15 V, R _L = 3 Ω I _D ≅ 5 A, V _{GEN} = 4.5 V, R _g = 16 Ω	Ch 1		29	44	
			Ch 2		19	29	
Fall Time	t _f		Ch 1		13	20	
			Ch 2		26	39	
Drain-Source Body Diode Characteristics							
Continous Source-Drain Diode Current	I _S	T _C = 25 °C	Ch 1			2.5	A
			Ch 2			2.1	
Pulse Diode Forward Current ^a	I _{SM}		Ch 1			20	
			Ch 2			20	
Body Diode Voltage	V _{SD}	I _S = 1.6 A	Ch 1		0.77	1.2	V
		I _S = 1.6 A	Ch 2		0.79	1.2	
Body Diode Reverse Recovery Time	t _{rr}	Channel 1 I _F = 2 A, dl/dt = 100 A/μs, T _J = 25 °C	Ch 1		21	42	ns
			Ch 2		18	36	
Body Diode Reverse Recovery Charge	Q _{rr}		Ch 1		15	30	nC
			Ch 2		11	22	
Reverse Recovery Fall Time	t _a	Channel 2 I _F = 2 A, dl/dt = 100 A/μs, T _J = 25 °C	Ch 1		13		ns
			Ch 2		11		
Reverse Recovery Rise Time	t _b		Ch 1		8		
			Ch 2		7		

Notes:

a. Guaranteed by design, not subject to production testing.






b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.




Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Output Characteristics (Ch 1)****Transfer Characteristics (Ch 1)****On-Resistance vs. Drain Current and Gate Voltage (Ch 1)****Capacitance (Ch 1)**




TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.







TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Ambient (Ch 1)




Normalized Thermal Transient Impedance, Junction-to-Case (Ch 1)

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage (Ch 2)




On-Resistance vs. Gate-to-Source Temperature (Ch 2)



Threshold Voltage (Ch 2)






Single Pulse Power, Junction-to-Ambient (Ch 2)




* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient (Ch 2)


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted T_C - Case Temperature (°C)**Current Derating* (Ch 2)** T_C - Case Temperature (°C)**Power Derating, Junction-to-Foot (Ch 2)** T_A - Ambient Temperature (°C)**Power Derating, Junction-to-Ambient (Ch 2)**

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Normalized Thermal Transient Impedance, Junction-to-Ambient (Ch 2)



Normalized Thermal Transient Impedance, Junction-to-Case (Ch 2)

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg273849.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.