


LENGTH TOLERANCE FOR CABLE ASSEMBLIES	
Inches	Millimeters
0 - 2IN +/- 0.040	0 - 51 +/- 1
2IN - 6IN +/- 0.080	51 - 153 +/- 2
6IN - 12IN +/- 0.140	153 - 305 +/- 3.5
12IN - 48IN +/- 0.250	305 - 1219 +/- 6.4
48IN - 144IN (12FT) +/- 0.500	1219 - 3658 +/- 13
144IN (12FT) - ABOVE +/- 1.0	3658 - ABOVE +/- 25
UNLESS OTHERWISE SPECIFIED ON DRAWING	


-XX IN THE ENDING OF THE CABLE PART NUMBER IS CALLING OUT THE LENGTH OF THE ASSEMBLY FROM CENTER TO MATING FLANGE OF CONNECTORS. EXAMPLES SHOWN BELOW:

LTI P/N: CBQ1-SALF3GT-SALRF3GT-4IN (4 INCHES)
CBQ1-SALF3GT-SALRF3GT-100mm (100 MILLIMETERS)

REVISIONS				
REV	ECR	DESCRIPTION	DRAWN	DATE
1		ENGINEERING RELEASE	M. LARSEN	7/31/2024



ITEM	PART NUMBER	DESCRIPTION	QTY
1	SALF13RGT-316	SMA, RIGHT ANGLE, JACK, BLKHD MNT, CABLE CRIMP	1
2	SALRF13RGT-316	RP-SMA, RIGHT ANGLE, REV POL JACK, BLKHD MNT, CABLE CRIMP	1
3	LTI-100	CABLE, LTI-100 COAX (LMR-100 Equivalent)	AR
4	1635F-3/16"	.1875 (3/16) DIA, .75 LENGTH, GREEN	2

DO NOT SCALE DRAWING			 Lighthouse Technologies San Diego, CA WWW.RFCONNECTOR.COM			
TOLERANCES UNLESS OTHERWISE SPECIFIED						
DIMENSIONS ARE IN MILLIMETERS						
X = ±0.5 X.X = ±0.25 X.XX = ±0.13 ANGLE = ±30°		 THIRD ANGLE PROJECTION	TITLE: CABLE ASSEMBLY, SMA, R/A JACK, BLKHD MNT, CRIMP TO RP-SMA, R/A JACK, BLKHD MNT, CRIMP USING LTI-100 CABLE			
CUSTOMER APPROVAL						
SIGN / DATE:						
ENG APPR.			SIZE	PART/DWG. NO:		REV
CHECKED			B	CBQ1-SALF3GT-SALRF3GT-xx		1
DRAWN		M. LARSEN		7/31/2024		
		NAME		DATE		
			SCALE: 2:1		FILE NAME	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
UNLESS OTHERWISE SPECIFIED: THIS DOCUMENT CONTAINS LIGHTHORSE TECHNOLOGIES INFORMATION. REPRODUCTION, USE, DISCLOSURE OR TRANSMITTAL OF ALL OR ANY PART OF THIS DOCUMENT IS PROHIBITED EXCEPT TO THE EXTENT APPROVED IN WRITING BY AN AUTHORIZED REPRESENTATIVE OF LIGHTHORSE TECHNOLOGIES. LIGHTHORSE TECHNOLOGIES RESERVES ALL RIGHTS UNDER PATENTS, TRADEMARKS, COPY RIGHTS AND TRADE SECRETS. COPY RIGHTS OF LIGHTHORSE TECHNOLOGIES 2011, ALL RIGHTS RESERVED.

