

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△				..	△				..
△				..	△				..

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-30℃ TO +85℃ (NOTE1)	STORAGE TEMPERATURE RANGE	-10℃ TO +60℃
	VOLTAGE	250 V DC	APPLICABLE CONTACT	—
	CURRENT	3 A	APPLICABLE CONNECTOR	—
			APPLICABLE CABLE	UL1061 24 AWG TO 28 AWG

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	Q	T	A	T	
CONSTRUCTION							
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	○	○			
MARKING	CONFIRMED VISUALLY.		○	○			
ELECTRICAL CHARACTERISTICS							
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	30 mΩ MAX.	○	—			
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX. mA (DC OR 1000 Hz).	mΩ MAX.	—	—			
INSULATION RESISTANCE	500 V DC	1000 MΩ MIN.	○	—			
VOLTAGE PROOF	650 V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN.	○	—			
MECHANICAL CHARACTERISTICS							
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.	INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.	—	—			
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.	—	—			
MECHANICAL OPERATION	TIMES INSERTIONS AND EXTRACTIONS	① CONTACT RESISTANCE: mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	—	—			
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm. - m/s ² AT 2 h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF μs. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	○	—			
SHOCK	AT m/s ² DURATION OF PULSE TIMES FOR DIRECTIONS. ms	① NO ELECTRICAL DISCONTINUITY OF μs. ② CONTACT RESISTANCE: mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	—	—			
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2℃, 90~95% 96 h.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	○	—			
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→-5~35→+85→5~35℃ TIME 30→5→30→5 min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	○	—			
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, IMMERSION, DURATION. ℃ FOR s.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	—	—			
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, FOR IMMERSION DURATION. s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.	—	—			
REMARKS							
NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.			DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
Unless otherwise specified, refer to MIL-STD-1344.			T. Miyazaki 95.4.17	T. Miyazaki 95.4.17	J. Oma 95.4.18	M. Yamano 95.4.18	
Note QT: Qualification Test AT: Assurance Test ○: Applicable Test							
HRS HIROSE ELECTRIC CO., LTD.			SPECIFICATION SHEET		PART NO. DF4-※DP-2C		
CODE NO. (OLD) CL	DRAWING NO. ELC4-160366	CODE NO. 0078-3 C L 544-0092-4			1/1		(INC)