



- NOTES 1. LEAD CO-PLANARITY SHALL BE 0.1mmMAX.
2. PER REEL : 5000 COMPONENTS.
3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
4. REFER TO JIS 0806.(PACKING OF COMPONENTS FOR AUTO HANDRING)
5. DO NOT MOUNT ANY OTHER COMPONENTS TO THE INDICATED AREA WHEN USING OUR RECOMMENDED TOOL.
6. LOCATION OF THE CONNECTOR AND RECOMMENDED PCB LAYOUT ARE ALIGNED WITH THOSE CENTERS.

2	LCP	UL94V-0, BLACK	6	PS	BLACK
1	PHOSPHOR BRONZE	CONTACT AREA : Au PLATING 0.1μmMIN LEAD AREA : Au PLATING 0.05μmMIN UNDER PLATING : Ni PLATING 1μmMIN	5	POLYESTER	CLEAR
			4	PS	CLEAR
			3	PHOSPHOR BRONZE	WHOLE AREA : Sn PLATING 1μmMIN UNDER PLATING:Cu PLATING 0.3μmMIN
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
		FREE					
 HIROSE ELECTRIC CO., LTD.	APPROVED : TS. SAKATA		12. 06. 12	DRAWING NO.	EDC3-344840-01		
	CHECKED : HS. OZAWA		12. 06. 12	PART NO.	DF56C-30S-0. 3V(51)		
	DESIGNED : TP. MATSUMOTO		12. 06. 12	CODE NO.	CL662-5616-0-51		
	DRAWN : TP. MATSUMOTO		12. 06. 12		 1/		

