Apr.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	−25°C TO +85°C	STORAGE TEMPERATURE RANGE	−25°C TO +60°C
	VOLTAGE		APPLICABLE CABLE	1 CABLE DIAMETER : φ5.1～7.1
	CURRENT			

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1	2	DIS-E-00003216	KN. ICHIKAWA	TU. TANIGUCHI	20201019

REMARK
THIS PRODUCT SHALL BE MATED WITH DH30B-17S, IT APPLIES TO DH30B-17S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.

Unless otherwise specified, refer to IEC 60512. 1

APPROVED	AO. SUZUKI	20090511
CHECKED	KN. ICHIKAWA	20090511
DESIGNED	MO. SHIMOYAMA	20090511
DRAWN	MO. SHIMOYAMA	20090511

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-126946-00

HRS

SPECIFICATION SHEET

HIROSE ELECTRIC CO., LTD.

PART NO. DH-17-CT2B

CODE NO. CL244-0047-5-00 1

FORM HD0011-2-1