

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE		-25℃ TO +85℃	STORAGE TEMPERATURE RANGE	-25℃ TO +60℃
	OPERATING&STORAGE HUMIDTY RANGE		85%MAX	APPLICABLE CABLE	CABLE DIAMETER : ϕ 7.3~9.3
	CURRENT			VOLTAGE	
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X
MARKING		CONFIRMED VISUALLY.			X X
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
2	DIS-E-00003216		KN. ICHIKAWA	TU. TANIGUCHI	20201019
REMARK THIS PRODUCT SHALL BE MATED WITH DH3*B-37S, IT APPLIES TO DH3*B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to IEC 60512.			APPROVED	A0. SUZUKI	20090428
			CHECKED	KN. ICHIKAWA	20090428
			DESIGNED	MO. SHIMOYAMA	20090428
			DRAWN	MO. SHIMOYAMA	20090428
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126854-00
	SPECIFICATION SHEET		PART NO.	DH-37-CT1B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0041-9-00	1/1