

APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE	-25℃ TO +85℃	STORAGE TEMPERATURE RANGE	-25℃ TO +60℃			
	OPERATING&STORAGE HUMIDTY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : ϕ9.6±0.5			
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT AT	
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X X	
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	DATE	
REMARK Unless otherwise specified, refer to JIS C 5402.				APPROVED	A0. SUZUKI	09. 10. 05	
				CHECKED	KN. ICHIKAWA	09. 10. 02	
				DESIGNED	TU. TANIGUCHI	09. 10. 02	
				DRAWN	TU. TANIGUCHI	09. 10. 02	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126660-00		
	SPECIFICATION SHEET		PART NO.	DH-51-CMB (9. 6)			
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0034-3-00		1/	