

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD			
POWER	2 W	CHARACTERISTIC IMPEDANCE	50 Ω
OPERATING TEMPERATURE RANGE	-40°C TO +85 °C	STORAGE TEMPERATURE RANGE	-40°C TO +70 °C
FREQUENCY RANGE	DC TO 6000 MHz	OPERATING HUMIDITY RANGE	% TO 90 %
CURRENT		APPLICABLE CABLE	

SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT

CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	×	×
MARKING	CONFIRMED VISUALLY.		—	—

ELECTRIC CHARACTERISTICS				
VSWR	FREQUENCY DC TO 3000 MHz.	1.25 MAX	×	—
※1	FREQUENCY 3000 TO 6000 MHz.	1.4 MAX		
INSERTION LOSS	FREQUENCY DC TO 3000 MHz.	0.3dB MAX	×	—
※1	FREQUENCY 3000 TO 6000 MHz.	0.5dB MAX		
ISOLATION	FREQUENCY TO MHz.	MIN	—	—
CONTACT RESISTANCE	VALUE AT MAXIMUM OF DC 100 mA	CENTER 30 mΩ MAX OUTER 30 mΩ MAX	×	—
INSULATION RESISTANCE	VALUE AT DC 100 V MIN.	1000 MΩ MIN	×	—
VOLTAGE PROOF	MUST KEEP THE AC 100 V FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	×	×

MECHANICAL CHARACTERISTICS				
DURABILITY	MUST BE LESS THAN THE STD.VALUE AFTER 500 TIMES INSERTION AND EXTRACTIONS AT THE CONDITION.	① CONTACT RESISTANCE: CENTER 30 mΩ MAX OUTER 30 mΩ MAX ② JUST NOT HAVE HEAVY CORROSION.	×	—

REMARKS		DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
※1 : This spec is under mated condition with MS-156-HRMJ-3.		K. Hida	K. Hida	K. Kawamura	Y. Nishida	
Unless otherwise specified, refer to IEC-60512.		03.5.23	03.5.23	03.5.23	03.5.24	
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test						

HS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO. MS-156R-HRMJ-1	
CODE NO.(OLD) CL	DRAWING NO. ELC4 -180354	PART NO.	CL358-0188-8	1/1	

TO
RFD