





NOTE 1. () INDICATES THE REFERENCE DIMENSIONS.
2. COLORS ARE SHOWN IN TABLE-1.
3. PER PACK: 50 PIECES.

TABLE-1


PART No.	HRS No.	COLOR
TM21P-88P(11)	CL222-2862-9-11	LIGHT BEIGE
TM21P-88P(12)	CL222-2862-9-12	MEDIUM GRAY
TM21P-88P(13)	CL222-2862-9-13	BLACK
TM21P-88P(14)	CL222-2862-9-14	NATURAL LIGHT GRAY
TM21P-88P(15)	CL222-2862-9-15	RED
TM21P-88P(16)	CL222-2862-9-16	GREEN
TM21P-88P(17)	CL222-2862-9-17	BLUE
TM21P-88P(18)	CL222-2862-9-18	YELLOW
TM21P-88P(19)	CL222-2862-9-19	ORANGE
TM21P-88P(32)	CL222-2862-9-32	WHITE
TM21P-88P(33)	CL222-2862-9-33	VIOLET
TM21P-88P(34)	CL222-2862-9-34	PINK

ATTACHED HOOD CLOSED




HOOD ATTACHMENT PROCEDURE (FREE)

1. FIT THE OPENED HOOD ON THE CABLE AND CLOSE. HOOD DIRECTION IS SHOWN AS AN EXAMPLE.



2. SLIDE THE CLOSED HOOD TO THE PLUG LOCK POSITION UNTIL BEING LOCKED AT A.



NO.			1			(2) UL94V-2		
MATERIAL			POLYAMIDE					
FINISH . REMARKS								
UNITS	mm	SCALE	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
		2 : 1	3	DIS-E-001276		TS. ITO	HO. MIWA	07. 02. 14
HRS HIROSE ELECTRIC CO., LTD.			APPROVED : HO. MIWA		05. 01. 05	DRAWING NO. EDC3-121484-01		
			CHECKED : TH. KAMEYA		05. 01. 05	PART NO. TM21P-88P (**)		
			DESIGNED : SS. SATOH		05. 01. 05	CODE NO.		
			DRAWN : SS. SATOH		05. 01. 05			